

# DLV7100/7200/8100/8200 115V series ■ For Machine Screws (2.6mm~6mm)

DLV7100/7200/8100/8200(115V)series



## Features

Complied with CNS standard of Taiwan, The Republic of China No. 13783-1

- A space saving model without transformer. High repetitive torque accuracy.
- The lever start type DLV7100/7200 series is useful for assembly requiring temporary screw tightening.

- The DLV8100/8200 series is the push to start type that is useful for continuous screw tightening.
- High speed type DLV7251/8251 series with a grip for tightening 6 mm machine screws is available.

## Specifications

Screwdriver	Model	Standard			High Speed			High Torque	Standard			High Torque	High Speed			High Torque	
		DLV7120-LJT	DLV7130-LJT	DLV7140-LJT	DLV7221-LJT	DLV7231-LJT	DLV7241-LJT	DLV7251-LJT	DLV8120-LJT	DLV8130-LJT	DLV8140-LJT	DLV8150-LJT	DLV8221-LJT	DLV8231-LJT	DLV8241-LJT	DLV8251-LJT	
	Bit Shank: Hex.5mm																
	Bit Shank: Hex. 6.35mm																
	Starting Method	Lever Start							Push to Start								
	Input Voltage	115VAC, 50/60Hz															
	Torque Adjustment	Stepless															
	Torque (N·m)	0.25-0.75	0.5-1.7	1.2-3.0	0.35-0.7	0.5-1.7	1.2-3.0	2.0-4.5	0.25-0.75	0.5-1.7	1.2-3.0	2.0-4.5	0.35-0.7	0.5-1.7	1.2-3.0	2.0-4.5	
	Free Speed (min <sup>-1</sup> )	900	900	600	1,800	1,800	1,100	700	900	900	600	400	1,800	1,800	1,100	700	
	Power Consumption (W)	Approx. 35			Approx. 45				Approx. 35			Approx. 45					
	Screw Size (mm)	Machine Screw	2.6~3	2.6~4	3.5~5	2.6~3	2.6~4	3.5~5	4.5~6	2.6~3	2.6~4	3.5~5	4.5~6	2.6~3	2.6~4	3.5~5	4.5~6
		Tapping Screw	2.3~3	2.3~3.5	3~4	2.3~3	2.3~3.5	3~4	4~5	2.3~3	2.3~3.5	3~4	4~5	2.3~3	2.3~3.5	3~4	4~5
	Bit Type	For LJT															
		For LKT															
	Mass (g)	700			700				890	690			890	690			890

\*1 : All models of LJT / LKT series are made to order.

\*2 : Only Chinese instruction manual is available for LJT / LKT series.

## Standard Accessories

	No.	LJT	LKT except DLV7251/8150/8251-LKT	DLV7251/8150/8251-LKT
Bit	No.1 x 6 x 70	1	—	—
	No.1 x 7 x 75	—	1	—
	No.2 x 6 x 70	1	—	—
	No.2 x 7 x 75	—	1	1
	No.3 x 7 x 50	—	—	—
Spare Carbon Brush			2	
Suspension Bail			1	

## External Dimensions

