

Electric screwdrivers bearing **CCC mark** (China Compulsory Certification mark) are available exclusively for China market.



Specifications

| | | | | High Torque | High Speed | | | | |
|----------------------|---------------------------------|--|-------------|-------------|-------------|--------------------------------------|-------------|-------------|--|
| Electric Screwdriver | Model (220V) | Lever Start | DLV7120-JJC | DLV7130-JJC | DLV7140-JJC | DLV8150-JJC | DLV8231-JJC | DLV8241-JJC | |
| | | Push to Start | DLV8120-JJC | DLV8130-JJC | DLV8140-JJC | DLV8150-JJC | DLV8231-JJC | DLV8241-JJC | |
| | | Lever Start | DLV7120-JKC | DLV7130-JKC | DLV7140-JKC | DLV8150-JKC | DLV8231-JKC | DLV8241-JKC | |
| | | Push to Start | DLV8120-JKC | DLV8130-JKC | DLV8140-JKC | DLV8150-JKC | DLV8231-JKC | DLV8241-JKC | |
| | Torque Adjustment | | Stepless | | | | | | |
| | Torque (N·m) | | 0.25~0.75 | 0.5~1.7 | 1.2~3.0 | 2.0~4.5 | 0.5~1.7 | 1.2~3.0 | |
| | Free Speed (min ⁻¹) | | 900 | | 600 | 400 | 1,800 | 1,100 | |
| | Power Consumption (W) | | 35 | | | | | | |
| | Screw Size (mm) | Machine Screw | 2.6~3 | 2.6~4 | 3.5~5 | 4.5~6 | 2.6~4 | 3.5~5 | |
| | | Tapping Screw | 2.3~3 | 2.5~3.5 | 3~4 | 4~5 | 2.5~3.5 | 3~4 | |
| Mass (g) | | 700 (7100series), 690 (8100 series) | | | 890 | 700 (7200 series), 690 (8200 series) | | | |
| Standard Accessories | | Each 1pc.of bit No.1×6×70 / No.2×6×70 (In the case of DLV7251 / 8150 / 8251 each 1pc.of No.2×7×75 / No.3×7×50) 1pc. Suspension Bail, 2pcs. Carbon Brush | | | | | | | |

| | | |
|----------|--|--|
| Bit (mm) | | |
|----------|--|--|

| Electric Screwdriver | | DLV7321-CMC | DLV7331-CMC | DLV7321-CKC | DLV7331-CKC |
|---------------------------------|---------------|-------------|-------------|-------------|-------------|
| Starting Method | | Lever Start | | | |
| Input Voltage | | 24VDC | | | |
| Torque Adjustment | | Stepless | | | |
| Torque (N·m) | | 0.05~0.5 | 0.3~1.2 | 0.05~0.5 | 0.3~1.2 |
| Free Speed (min ⁻¹) | | 700~1,000 | 500~700 | 700~1,000 | 500~700 |
| Power Consumption (W) | | 26 | | | |
| Screw Size (mm) | Machine Screw | 1~3 | 2~3.5 | 1~3 | 2~3.5 |
| | Tapping Screw | 1.2~2.6 | 2~3 | 1.2~2.6 | 2~3 |
| Bit (mm) | | | | | |
| Mass (g) | | 350 | | | |

| | | |
|------------|------------------|--------------------------------------|
| Controller | Model | DLC1213-GC |
| | Input Voltage | AC 220V |
| | Control Function | Auto Stop, Soft Start, Speed Control |
| | Mass (g) | 2300 |

| Electric Screwdriver | | DLV5720C | DLV5720HC | DLV5740C | DLV5740HC | DLV5750C |
|---------------------------------|---------------|--|-----------|----------|--|-----------|
| Starting Method | | Lever Start | | | | |
| Torque Adjustment | | Stepless | | | | |
| Torque (N·m) | | 0.02~0.2 | | 0.15~0.4 | | 0.1~0.55 |
| Free Speed (min ⁻¹) | | 500~750 | 700~1,000 | 450~600 | 1,200~1,800 | 670~1,000 |
| Power Consumption (W) | | 10 | | | 26 | |
| Screw Size (mm) | Machine Screw | 1.0~2.3 | | 1.6~2.6 | | 1.0~3.0 |
| | Tapping Screw | 1.0~2.0 | | 1.4~2.3 | | 1.0~2.6 |
| Bit (mm) | | | | | | |
| Mass (g) | | 230 | | | 300 | |
| Standard Accessories | | Bit (No.0×1.8×44·No.0×2.5×44) Each 1 piece Connection Cable (1.5M) DLW9081 : 1piece Suspension Bail : 1 piece Spring for Low Torque : 1 piece | | | Bit (No.0×2.5×44·No.1×4×44) Each 1 piece Connection Cable (1.5M) DLW9081 : 1 piece Suspension Bail : 1 piece | |
| Model | | DLC0350GC | | | DLC0950GC | |
| Input Voltage | | AC 220V | | | | |
| Mass (g) | | 900 | | | 1800 | |

※ The Controller incorporates the safe resistance that is installed between the bit and the power source cord.