

Screwdrivers designed for DLR5640-WN

■ Screw Fastening Counter



DLR5640-WN



DLV7410A / 7410HA / 7420A-SPC



DLV7321 / 7331-SPC

Specifications

Model	DLV7410A-SPC	DLV7410HA-SPC	DLV7420A-SPC	DLV7321-SPC	DLV7331-SPC
Starting method	Lever start switch				
Torque Adjustment	Stepless				
Torque (N·m)	0.02 ~ 0.20		0.15 ~ 0.40	0.10 ~ 0.50	0.30 ~ 1.20
Free speed (min ⁻¹)	500 ~ 750	700 ~ 1000	450 ~ 600	300 ~ 1000	200 ~ 700
Power Consumption (W)	10			26	
Screw Size (mm)	Machine Screw	M1.0 ~ 2.3	M1.6 ~ 2.6	M1.0 ~ 3.0	M2.0 ~ 3.5
	Tapping Screw	M1.0 ~ 2.0	M1.4 ~ 2.3	M1.2 ~ 2.6	M2.0 ~ 3.0
Bit type (mm)					
Electrostatic countermeasure	Complied with EN100015-1				
Mass (kg)	0.23			0.35	
Cord length (m)	1.5 (with connector)				
Output signals	Start, Torque up, Reverse				
Grounding bit feature	Equipped as standard				

Combinations with electric screwdrivers

Screwdriver model	Connection	Remarks
DLV7410A / 7410HA / 7420A-SPC	The cord comes with screwdriver	Screwdriver for the screw fastening counter only
DLV7321 / 7331-SPC	Direct connection to power source	
DLV7410A / 7410HA / 7420A / 7419 / 7419HA / 7429-BMN	Optional conversion cord (TD02925 DLW9072)	General-purpose screwdriver *1
DLV7321 / 7331-BMN *2	Direct connection to power source	
DLV7313 / 7323 / 7333 / 7321 / 7331 / 7325 / 7335-CMN *2	Optional conversion cord (TD02826)	

*1: The Count Return Function is not available.

*2: When used with DLV732□ series, the torque adjust ring of screwdriver should be set more than torque scale 3.

Optional cord



TD02925 DLW9072



TD02826 Conversion cord from 5-pin to 6-pin.