

# Screwdrivers designed for DLR5640-WN

■ Screw Fastening Counter



DLR5640-WN



DLV7410A/7410HA/7420A-SPC



DLV7321/7331-SPC

## Specifications

Model		DLV7410A-SPC	DLV7410HA-SPC	DLV7420A-SPC	DLV7321-SPC	DLV7331-SPC
Starting Method		Lever Start				
Torque Adjustment		Stepless				
Torque	(Nm)	0.02 - 0.2		0.15 - 0.4	0.1 - 0.5	0.3 - 1.2
Free Speed	(min <sup>-1</sup> )	500 - 750	700 - 1,000	450 - 600	300 - 1,000	200 - 700
Power Consumption		Approx. 10			Approx. 35	
Screw Size	Machine Screw	1.0 - 2.3		1.6 - 2.6	1.0 - 3.0	2.0 - 3.5
	Tapping Screw	1.0 - 2.0		1.4 - 2.3	1.2 - 2.6	2.0 - 3.0
Bit Type	(mm)					
Electrostatic Countermeasure		Complied with EN100015-1				
Mass	(g)	230			350	
Cord Length	(m)	1.5 (with connector)				
Grounding Bit Feature		Equipped as standard				

## Combinations with Electric Screwdrivers

Screwdriver Model	Connection	Remarks
DLV7410A / 7410HA / 7420A-SPC	The cord comes with screwdriver	Screwdriver for the screw fastening counter only
DLV7321 / 7331-SPC	Direct connection to power source	
DLV7410A / 7410HA / 7420A / 7419A / 7419HA / 7429A-BMN	Optional conversion cord (TD02925 DLW9072)	General-purpose screwdriver*1

\*1: The Count Return Function is not available.

## Optional Accessories



DLW9072(TD02925)



**Torque Adjustment Cover**  
(DLW5700:DLV7400A-SPC  
DLW5300:DLV7300-SPC)

Tampering or accidental turning of the torque adjustment cover by an operator can be prevented.

DLR5640-WN