

LINEAR



AC0301A



MOTOR FREE
PISTON SYSTEM



Airflow & Power Consumption




Specifications


	(SI)	(EURO)	(U.S.A.)
Rated Pressure	0.01 MPa {0.1 kgf/cm ² }	0.1 bar	1.42 psig
Rated Airflow	28 ℓ /min		
Rated Voltage	115 V, AC or 230 V, AC		
Maximum Pressure	0.03 MPa {0.3 kgf/cm ² }	0.3 bar	4.27 psig
Power Consumption	25 W or 29 W		
Rated Frequency	60 Hz or 50 Hz		
Life Expectancy	10,000 hours		
Outlet	ISO Rc 1/4 (female threaded)		
Duty Cycle	Continuous		
Coil Insulation Class	E or its equivalent (JETL) or B for UL		
Mounting Dimensions	68 (L) x 84 (W) mm		
Gross Weight	1.9 kg	4.2 Lbs.	
Leadwire Length	200 mm	7-7/8"	

* Life expectancy is the expected accumulated period of time during which the compressor will maintain the above specifications. Contact your supplier for details of the conditions of use under which the values and numbers stated herein are maintained.

Application Examples



Liquid Mixer



Seat Lifter

Sketch Drawing and Mounting Dimensions Diagram (mm)

