


LINEAR


Ac0901

 
**MOTOR FREE
 PISTON SYSTEM**




Airflow & Power Consumption

Specifications




	(SI)	(EURO)	(U.S.A.)
Rated Pressure	0.01 MPa {0.1 kgf/cm ² }	0.1 bar	1.42 psig
Rated Airflow	80 l/min		2.83 cfm
Rated Voltage	115 V, AC or 230 V, AC		
Maximum Pressure	0.04 MPa {0.4 kgf/cm ² }	0.4 bar	5.69 psig
Power Consumption	88 W or 99 W		
Rated Frequency	60 Hz or 50 Hz		
Life Expectancy	10,000 hours		
Outlet	ISO Rc 3/8 (female threaded)		
Duty Cycle	Continuous		
Coil Insulation Class	E or its equivalent (JETL) or B for UL		
Mounting Dimensions	102 (L) x 130 (W) mm		
Gross Weight	4.9 kg		10.8 Lbs.
Leadwire Length	300 mm		11-13/16" for 115V


* Life expectancy is the expected accumulated period of time during which the compressor will maintain the above specifications. Contact your supplier for details of the conditions of use under which the values and numbers stated herein are maintained.



Application Examples



Pneumatic Jack



Gas Burner Booster

Sketch Drawing and Mounting Dimensions Diagram (mm)

