

DIAPHRAGM PUMP


DIAPHRAGM PUMP



vc0100 Blower Type

Airflow & Power Consumption


Specifications



	(SI)	(EURO)	(U.S.A.)
Rated Pressure	0.004 MPa (0.04 kgf/cm ²)	0.04 bar	0.57 psig
Rated Airflow	6 l/min		0.21 cfm
Rated Voltage	120 V AC or 230 V AC		
Maximum Pressure	0.016 MPa (0.16 kgf/cm ²)	0.16 bar	2.28 psig
Power Consumption	6 W		
Rated Frequency	60 Hz or 50 Hz		
Life Expectancy	10,000 hours		
Working Pressure Range	0~0.016 MPa {0~0.16 kgf/cm ² }	0~0.16 bar	0~2.28 psig
Outlet (or Inlet)	6 mm O.D. hose nipple		
Duty Cycle	Continuous		
Coil Insulation Class	E for 230V & A for 120V or its equivalent		
Mounting Dimensions	70 (L) x 72 (W) mm	2-3/4" (L) x 2-27/32" (W)	
Gross Weight	0.45 kg		0.99 Lbs.
Leadwire Length	300 mm		11-13/16"

Please read the page of "How to Use This Catalog" first for correct use of compressors and pumps.

Application Examples



Sketch Drawing and Mounting Dimensions Diagram (mm)

