


MAF401A / D / M series


AIR UNITS (Air / Mist / Micromist Filter)




Symbol



A : 5 μ m



D : 0.3 μ m



M : 0.01 μ m

- MAF401A is designed for draining and removal of foreign matter. (Element : 5 μ m)
- MAF401D/M is designed for removal of foreign matter as well as oil mist (Element : 0.3 μ m / 0.01 μ m)

Specification

Model	MAF401A/D/M		
Bore No.	8A	10A	15A
Port size	1/4	3/8	1/2
Medium	Air		
Operating pressure range (※)	0.05~1.5 MPa		
Proof pressure	2 MPa		
Ambient temperature	-5~+60°C (No freezing)		
Filter element	5 μ m, 0.3 μ m, 0.01 μ m		
Weight	480 g		

※ 1. Standard unit contains semi-auto-drain function when operating pressure below 0.05 MPa.

※ 2. Choose auto-drain FMRF300, the pressure range is 0.15 ~ 1 MPa.

Order example

MAF401D - 8A - □ - B - □

MODEL

BORE SIZE

8A: 1/4
10A: 3/8
15A: 1/2

B: C type bracket

PORT THREAD

Blank: Rc thread
G: G thread
NPT: NPT thread

FILTER ELEMENT

A: 5 μ m
D: 0.3 μ m
M: 0.01 μ m

D: auto drain valve (FMRF300)

Option accessories

C type bracket

