

BARRIER WRENCHES


The unique "MERRY" Barrier Wrenches have solved the problem of difficult bolt / nut fastening and loosening jobs in narrow and hard-to-reach places.


(Fastening torque is transferred through a chain.)




Grip the handles of both Barrier Wrench and ratchet wrench together for multiplied power.








General use with ratchet wrench






Impact Wrench can be used instead of a ratchet wrench **only for YL2.** (Torque should not exceed 180N-m.)




00(

000

XXXXX








Model No.	Square size A × B	С	D	Е	F	G	Н	1	K	Weight	Max, allowable torque
YL1A	凸 9.5□×凹 9.5□	300	217	39	150	φ 20	18	22	10	820g	94N-m (9.6kgf-m)
YL1B	凸 12.7 [□] × 凹9.5 [□]	300	217	39	150	φ 20	18	22	14		
YL2	凸 12.7 [□] ×凹 12.7 [□]	327	228	49	210	φ 26	20	25	14	1,330g	196N-m (20kgf-m)
YL2A										1,030g	

AN EXAMPLE OF APPLICATION


Barrier Wrenches offer safe and smooth service for replacement or adjustment of the cultivator blades in narrow space.



OTHER EXAMPLES OF APPLICATION



Machine installation



Piping construction

