



Models and Dimensions

Plug Female thread



Model	Application	Mass (g)			Dimensions (mm)				
		Steel	Brass	Stainless steel	Lp	C	A	Hp(WAF)	T
1P	R 1/8	19 +1	21	19	29	19	11	Hex.14	Rc 1/8
2P	R 1/4	35	38	35	36	22	13	Hex.17	Rc 1/4
3P	R 3/8	60	65	60	40	25	13	Hex.21	Rc 3/8
4P	R 1/2	123	134	124	44	28	15	Hex.29	Rc 1/2
6P	R 3/4	212	231	213	52	36	17	Hex.35	Rc 3/4
8P	R 1	350	381	332	62	40	20	Hex.41	Rc 1
10P	R1 1/4	590	610	590	70	45	24	Hex.54 +3	Rc1 1/4
12P	R1 1/2	820	880	840	75	49	24	Hex.63 +2	Rc1 1/2
16P	R 2	1430	1530	1450	80	52	27	Two flats 77x ø84	Rc 2

Socket Female thread



Model	Application	Mass (g)			Dimensions (mm)				
		Steel	Brass	Stainless steel	Ls	øD	A	Hs(WAF)	T
1S	R 1/8	85 +1	93	86	48	24	11	Two flats 14 x ø18	Rc 1/8
2S	R 1/4	133	145	134	58	28	13	Two flats 19 x ø22	Rc 1/4
3S	R 3/8	208	227	209	65	35	13	Two flats 21 x ø25	Rc 3/8
4S	R 1/2	428	466	431	72	45	15	Two flats 29 x ø35	Rc 1/2
6S	R 3/4	710	773	714	88	55	17	Two flats 35 x ø41	Rc 3/4
8S	R 1	1000	1089	980	102	65	20	Two flats 41 x ø48	Rc 1
10S	R1 1/4	1570	1680	1580	115	77	24	Two flats 54 x ø59	Rc1 1/4
12S	R1 1/2	2320	2490	2350	124	88	24	Two flats 63 x ø69	Rc1 1/2
16S	R 2	3590	3860	3620	132	108	27	Two flats 77 x ø86	Rc 2

*1 : 1-S and 1-P steel are made-to-order items. *2 : Stainless steel: Hex.63 x 67mm dia. *3 : Stainless steel: Hex.54 x 59mm dia.
 • Semi-standard stainless steels (SUS304, 316) have different appearances from the above drawings.

Application example

