### For Low Pressure (Air)

## **Purge Line Cupla**

Simple air line coupling manifold with residual pressure release function







# Residual pressure can be released by a mere lever turn. Very smooth connection/disconnection!

- Single action, just push in the plug to connect regardless of internal pressure in socket.
- No unpleasant noise of air pressure discharge and no hose whip back motion on disconnection for safety operation.
- Safe design socket valve will not open or close unless plug is connected.
- Even after connection, a lever turn will open/close valve with perfect control
  of air flow or line shut-off.
- Enables simultaneous air supply to three outlets from a single air line.
   (A single outlet Purge Hi Cupla is also available see the pages of Purge Hi Cupla for details.)



Specifications							
Body material		Brass (Chrome-plated)					
Size		Inlet R 1/2					
		Outlet Socket (PV-30SM)					
Working pressure	MPa	1.0					
	kgf/cm <sup>2</sup>	10					
	bar	10					
	PSI	145					
Seal material Working temperature range		Seal material	Mark	Working temperature range	Remarks		
		Nitrile rubber	NBR (SG)	-20°C to +60°C	Standard material		

Max. Tightening Torque	e Nm {kgf•cm}
Size (Thread)	1/2"
Torque	30 {306}

### Flow Direction

Fluid must run from the intake port to the outlet ports. Please refer to the flow directions (arrows) on the " Models and Dimensions."

### Interchangeability

Can be connected with plugs for Hi Cupla Models 10, 17, 20, 30 and 40. Interchangeable with each corresponding Hi Cupla Series models.


Min. Cross-Sectional Area		(mm²)
	41	

### Suitability for Vacuum

Not suitable for vacuum application in either connected or disconnected condition.

### Pressure - Flow Characteristics

[Test conditions] •Fluid : Air •Temperature : Room temperature



# Models and Dimensions Socket RE-PV-30 type (For three outlets) Mass: 1,090g • Fluid must run in the direction of the arrow. (58) (41) (58) (41) (41) (50) (50) (41)