

SCALING

NEEDLE SCALER **JET CHISEL**

Model **JC-16** Lightweight Type



Model **JEX-24** Universal Type



Model **JEX-28** Heavy-duty Type



Model **JEX-2800A** Low-vibration Type



Specifications

Model	JC-16	JEX-24	JEX-28	JEX-2800A
Rated Air Pressure MPa (kgf/cm ²)	0.59 {6}	0.59 {6}	0.59 {6}	0.63 {6.4}
Air Consumption (No load) m ³ /min	0.15	0.27	0.35	0.43
Stroke Speed min ⁻¹	4,000	4,000	4,500	3,700
Needles to be used mm	2 OD x 150 (29pcs.)	2 OD x 180 (53pcs.) or 3 OD x 180 (23pcs.)	2 OD x 180 (66pcs.) or 3 OD x 180 (28pcs.) or 4 OD x 180 (14pcs.)	
Hose Size inch	3/8	3/8	3/8	3/8
Mass (Weight) kg	1.4	2.7	3.5	3.1

Standard Accessories	JC-16	JEX-24	JEX-28	JEX-2800A
	<ul style="list-style-type: none"> • Needle 2mm OD x 150 mm : 29 pcs. (Needle 2mm OD x 150 mm : 29 pcs. on the body) • Bushing PT3/8 x NPT3/8 : 1 pc. • Hose Nipple PT3/8 x 3/8 : 1 pc. 	<ul style="list-style-type: none"> • Needle 3mm OD x 180 mm : 23 pcs. on the body • 6 mm Hex. Socket Screw Key : 1 pc. • Bushing PT3/8 x NPT3/8 : 1 pc. • Hose Nipple PT3/8 x 3/8 : 1 pc. 	<ul style="list-style-type: none"> • Needle 4mm OD x 180 mm : 14 pcs. (Needle 3mm OD x 180 mm : 28 pcs. on the body) • Needle Supporter 4mm OD : 1pc. • Bushing : 1 pc. • Hose Nipple : 1 pc. 	<ul style="list-style-type: none"> • Needle 4mm OD x 180 mm : 14 pcs. (Needle 3mm OD x 180 mm : 28 pcs. on the body) • Needle Supporter 4mm OD : 1 pc. • Bushing : 1 pc. • Hose Nipple : 1 pc.

Electric Needle Scaler

Model **EJC-32A**



Standard Accessories	EJC-32A
	<ul style="list-style-type: none"> • Needle 3mm OD x 180 mm : 30 pcs. (15 pcs.) • 6 mm Hex. Socket Screw Key : 1 pc.

The same excellent performance as our air tool!

Operated with standard electric supply to households. Special long and slim barrel design suitable for narrow corners. Double-insulated motor does not need grounding. Free subhandle position best fit to your working situation.

Specifications

Model	EJC-32A	
Power Supply	115 VAC 60Hz	230 VAC 50Hz
Rated Power Consumption W	300	300
Rated Current A	2.8	1.4
Rated Duty minutes	30	
Stroke Speed min ⁻¹	3,000	
Needles to be used mm	2 OD x 180 (32 pcs.) or 3 OD x 180 (15 pcs.)	
Power Cord m	5	
Mass (Weight) kg	4.5	

Optional Needles



PN	Part Name	Q'ty	PN	Part Name	Q'ty	Model
TA98780	Needle 2 mm OD x 150 mm	100 pcs.	TP00338	Needle Supporter 2 mm OD	1 pc.	JT-20,
TA98781	Needle 2 mm OD x 180 mm	100 pcs.	TP00337	Needle Supporter 3 mm OD	1 pc.	JEX-20
TA9A213	Needle 2 mm OD x 300 mm	50 pcs.	TQ05210	Needle Supporter 2 mm OD	1 pc.	AJC-16
TA9A214	Needle 2 mm OD x 500 mm	50 pcs.	TQ04554	Needle Supporter 3 mm OD	1 pc.	
TA98782	Needle 3 mm OD x 180 mm	100 pcs.	TP00290	Needle Supporter 2 mm OD	1 pc.	JC-16
TA9A216	Needle 3 mm OD x 300 mm	50pcs.	TP02244	Needle Supporter 2 mm OD	1 pc.	JEX-24
TA9A217	Needle 3 mm OD x 500 mm	50pcs.	TP02245	Needle Supporter 3 mm OD	1 pc.	
TA9A218	Needle 3 mm OD x 800 mm	50pcs.	TP01499	Needle Supporter 2 mm OD	1 pc.	JEX-28,
TA98783	Needle 4 mm OD x 180 mm	50 pcs.	TP01461	Needle Supporter 3 mm OD	1 pc.	
TA9A220	Needle 4 mm OD x 300 mm	50 pcs.	TP01462	Needle Supporter 4 mm OD	1 pc.	EJC-32A
TA9A221	Needle 4 mm OD x 500 mm	50 pcs.	TP16475	Needle Supporter 2 mm OD	1 pc.	
			TP16301	Needle Supporter 3 mm OD	1 pc.	