

MYTON

A wide variety of models are available to a particular job!



Model **MAG-50** Depressed center wheel 125mm OD



- Rear exhaust system.
- Vibration-damping side handle.
- Spindle lock for the replacement of wheel.
- Plastic housing prevents cold hand.
- Side handle can be mounted to right or left.
- Built in governor.

Powerful Motor for fast and efficient grinding

Specifications

Model	MAG-50
Rated Air Pressure MPa {kgf/cm ² }	0.59 {6}
Air Consumption (No load) m ³ /min	0.87
Free Speed min ⁻¹ (rpm)	12,000
Depressed center wheel mm	125 OD
Hose Size inch	1/4
Mass (Weight) kg	2.2

Standard Accessories

• Air Hose Sub Ass'y : 1 set	• 4mm Hex. Socket Screw Key : 1 pc.
• Exhaust Hose Ass'y : 1 set	• Pin Face Wrench : 1 pc.
• Side Handle Ass'y : 1 set	• Bushing PT3/8 x NPT 3/8 : 1 pc.

Model **MAG-25B** Depressed center wheel 58mm OD



Model **MAGW-40** Depressed center wheel 100mm OD



Model **MAG-70** Depressed center wheel 180mm OD



Specifications

Model	MAG-25B	MAGW-40	MAG-70
Rated Air Pressure MPa {kgf/cm ² }	0.59 {6}	0.59 {6}	0.59 {6}
Air Consumption m ³ /min	0.4 (No load)	0.68 (No load) 0.82 (Load)	0.69 (No load) 1.15 (Load)
Free Speed min ⁻¹ (rpm)	22,000	13,000	7,100
Depressed center wheel mm	58 OD	100 OD	180 OD
Hose Size inch	1/4	3/8	1/2
Mass (Weight) kg	0.55	1.55	3.4

Standard Accessories

<ul style="list-style-type: none"> • Abrasive Wheel AC #80 : 1 pc. • 5 mm Hex. Socket Screw Key : 1 pc. • 14 mm Single Ended Spanner : 1 pc. • Bushing PT1/4 x NPT1/4 : 1 pc. 	<ul style="list-style-type: none"> • 6 mm Hex. Socket Screw Key : 1 pc. • 17 mm Single Ended Spanner : 1 pc. • Bushing PT3/8 x NPT3/8 : 1 pc. 	<ul style="list-style-type: none"> • 6 mm Hex. Socket Screw Key : 1 pc. • 10 mm Hex. Socket Screw Key : 1 pc. • 41 mm Single Ended Spanner : 1 pc. • Bushing PT1/2 x NPT1/2 : 1 pc.
---	--	---