

# PALM ORBITAL SANDER

Ergonomically designed plastic housing conforms to the operator's hand for greater control and comfort



Model **APS-125/150**



*Random orbital action produces a high-quality swirl-free finish*

- Extremely light. APS-125 weights just 690g.
- Simple structure for easy maintenance.
- Extermely low vibration.
- Adjustable speed.

### Applications

- Feather edging, metal preparation, and finishing work on body filler.
- Curved surface sanding and corner rounding in wood work.

### For Self Vacuum & Central Vacuum

Available from stock are Non Vacuum Models. You can modify Non Vacuum to Self Vacuum or Central Vacuum by adding a few extra parts.



**Self Vacuum**



**Central Vacuum**

### Specifications

Model		APS-125	APS-150
Rated Air Pressure	MPa (kgf/cm <sup>2</sup> )	0.59 (6)	0.59 (6)
Air Consumption (No load)	m <sup>3</sup> /min	0.45	0.45
Motor Free Speed	min <sup>-1</sup> (rpm)	10,000	10,000
Orbit Diameter	mm	5 OD	5 OD
Paper Size	mm	125 OD	150 OD
Mass (Weight)	kg	0.69	0.72
Pad Mass (Weight)	kg	0.10	0.12

### Standerd Accessories

- Spanner 17 : 1 pc.
- Bushing PT1/4 x NPT1/4 : 1 pc.