

Optional Accessories for HAND BEVELER / MINI BEVELER / CIRCUIT BEVELER

| | PN | Part Name | Sales Unit | Application model | Remarks |
|--|---------|-----------------------------------|------------|--|---|
| | TA9A093 | Insert 12.7 Ass'y | 12pcs./set | HB-15B | |
| | TA9A896 | Insert 12.7 with hole Ass'y | 10pcs./set | AMB-07 | |
| | TB01159 | Insert 12.7 with hole Ass'y | 10pcs./set | EMB-0307B, AMB-0307, AMBL-0307, ECB-0203 | |
| | TB01791 | Insert 12.7 Ass'y R2 | 10pcs./set | EMB-0307B, AMB-0307, AMBL-0307, ECB-0203 | |
| | TB01651 | Insert 12.7 Ass'y R3 | 10pcs./set | EMB-0307B, AMB-0307, AMBL-0307, ECB-0203 | |
| | TB01790 | Insert 12.7 Ass'y R4 | 10pcs./set | EMB-0307B, AMB-0307, AMBL-0307 | |
| | TA9A386 | Insert 9.525 with hole Ass'y | 10pcs./set | MB-03A, CB-02 | |
| | TA9A592 | Insert 9.525 Ass'y R2 | 10pcs./set | MB-03A, CB-02 | |
| | TA9A638 | Insert 9.525 Ass'y R3 | 10pcs./set | MB-03A | |
| | TA9A728 | Plate Ass'y for pipe | 1 set | HB-15B | For pipe 125~800 mm dia. |
| | TB02539 | Attachment for small dia. pipe | 1 set | EMB-0307B, AMB-0307, AMBL-0307 | For pipe 80~200 mm dia. |
| | TA9A594 | Inner head Ass'y | 1 set | MB-03A | For min. 100 mm dia. |
| | TB02857 | Guide sleeve 24 mm dia. Ass'y | 1 set | ECB-0203 | For chamfering R2 |
| | TB03097 | Plate Ass'y for straight line use | 1 set | ECB-0203 | |
| | TB02862 | Dust Box Ass'y | 1 set | ECB-0203 | Used with Plate Ass'y for straight line use |
| | TB03424 | Spanner T-9D | 1 pc. | MB-03A, CB-02 | |
| | TQ01683 | Spanner T-15D | 1 pc. | EMB-0307B, AMB-0307, AMBL-0307, ECB-0203 | |

QUICK CONNECTIVE COUPLINGS FOR PNEUMATIC TOOLS **HI CUPLA series**

HI CUPLA / HI CUPLA 200 (One-touch connection & Big flow rate type)



- One-way shut-off cupla with an automatic shut-off valve in the socket.
- Important parts are hardened for excellent wear resistance and durability.

| Plug | | | | P | S | Socket | | | |
|---|---------------|----------------------------------|------------------------|---|----------|-------------------------------------|---------------|----------|---------------|
| For hose connection | | 40PH | For 1/2" hose | | | For hose connection | | 40SH | For 1/2" hose |
| 17PH | For 1/4" hose | 400PH | For 1/2" hose | | | 17SH | For 1/4" hose | 400SH | For 1/2" hose |
| 20PH | For 1/4" hose | 600PH | For 3/4" hose | | | 20SH | For 1/4" hose | 600SH | For 3/4" hose |
| 30PH | For 3/8" hose | 800PH | For 1" hose | | | For female thread connection | | 40SM | For Rc 1/2" |
| For female thread connection | | 40PM | For Rc 1/2" | | | 10SM | For Rc 1/8" | 400SM | For Rc 1/2" |
| 10PM | For Rc 1/8" | 400PM | For Rc 1/2" | | | 20SM | For Rc 1/4" | 600SM | For Rc 3/4" |
| 20PM | For Rc 1/4" | 600PM | For Rc 3/4" | | | For male thread connection | | 20SF | For R 1/4" |
| 30PM | For Rc 3/8" | 800PM | For Rc 1" | | | 30SF | For R 3/8" | 600SF | For R 3/4" |
| For male thread connection | | 20PF | For R 1/4" | | | 40SF | For R 1/2" | 800SF | For R 1" |
| 30PF | For R 3/8" | 600PF | For R 3/4" | | | For hose connection | | 200-17SH | For 1/4" hose |
| 40PF | For R 1/2" | 800PF | For R 1" | | | 200-20SH | For 1/4" hose | 200-40SH | For 1/2" hose |
| For male thread connection (parallel thread) | | 20PFF | For G 1/4" | | | 200-30SH | For Rc 3/8" | | |
| Specifications | | | | | | For female thread connection | | | |
| Type | | Hi Cupla | Hi Cupla 200 | | | For female thread connection | | | |
| Body material | | Steel (chrome-plated) | Steel (chrome-plated) | | | 200-20SM | For Rc 1/4" | | |
| Size | | 1/8", 1/4", 3/8", 1/2", 3/4", 1" | 1/8", 1/4", 3/8", 1/2" | | | 200-30SM | For Rc 3/8" | | |
| Working pressure | | 1.5MPa | 1.0MPa | | | For male thread connection | | | |
| Pressure resistance | | 2.0MPa | 1.5MPa | | | 200-20SF | For R 1/4" | | |
| Packing material | | NBR | NBR | | | 200-30SF | For R 3/8" | | |
| Working temp.range | | -20°C~80°C | -5°C~60°C | | 200-40SF | For R 1/2" | | | |



HI CUPLA ACE

- Plastic Cuplas with a built-in locking mechanism!
- Pressure ratings comparable to steel Cuplas.



| Specifications | |
|---------------------|----------------------|
| Body material | Engineering plastics |
| Size | 1/4", 3/8", others |
| Working pressure | 1.5MPa |
| Pressure resistance | 2.0MPa |
| Packing material | NBR |
| Working temp.range | -5°C~60°C |

| Plastic Plug | | | | P | S | Hi Cupla Ace Socket | | | |
|---|--|-----------|---------------------------|---|---|---|---------------------------|----------|----------------------|
| For hose connection (PH) | | 20PH-PLA | For 1/4" hose | | | For hose connection (SH) | | HA-20SH | For 1/4" hose |
| | | 30PH-PLA | For 3/8" hose | | | HA-30SH | For 3/8" hose | | |
| For female thread connection (PM) | | 20PM-PLA | For Rc 1/4" | | | For female thread connection (SM) | | HA-20SM | For Rc 1/4" |
| | | 30PM-PLA | For Rc 3/8" | | | HA-30SM | For Rc 3/8" | | |
| For urethane hose with spring nut connection (PNG) | | 50PNG-PLA | For 5 ID x 8 OD hose | | | For urethane hose with spring nut connection (SNG) | | HA-50SNG | For 5 ID x 8 OD hose |
| | | 65PNG-PLA | For 6.5 ID x 10 OD hose | | | HA-65SNG | For 6.5 ID x 10 OD hose | | |
| | | 85PNG-PLA | For 8.5 ID x 12.5 OD hose | | | HA-85SNG | For 8.5 ID x 12.5 OD hose | | |
| For male thread connection (PF) | | 20PFF-PLA | For G 1/4" | | | Hi Cupla Ace T type (for 2 branches) | | HA-T | 20P-PLA / HA-65S x 2 |
| | | | | | | | | | |
| | | | | | | | | | |