

SPECIALTY

For High Viscosity & Adhesives

- ☆ For use with μ pressurized container
- ☆ VR models include a check valve to prevent depressurization after trigger-release; allowing continuous work & stability
- ☆ VR models provide separation of inlet pressure and cup pressure adjustment; allowing best combination of atomization & fluid output flow
- ☆ Ideally suited for tough-to-spray materials including high viscosity, glue, corrosive/water-based adhesives, etc.

MODEL	(mm)	(psi)	(1/min)	(mm)	(kw)
S-770V-01P	1.5				
S-770V-02P	1.7				
S-770V-03P	2.0				
S-770V-04P	2.5				
S-770VR-01P	1.5	35-40	270	300-400	1.5-2.2
S-770VR-02P	1.7				
S-770VR-03P	2.0				
S-770VR-04P	2.5				



▶ Ø3.0/3.5mm NOZZLE ALSO AVAILABLE AIR INLET: 1/4" PF/NPS (M) FLUID INLET: 3/8" PF/NPS (M)

- ☆ Multi-purpose spray gun for light or heavy paint materials

MODEL	(flmm)	(psi)	(1/min)	(mm)	(kw)
S-107D	1.4	2.4-3.0	232	170	0.4



PRESSURE POTS & TANKS

2 QUARTS

- ☆ Lightweight aluminum body
- ☆ Great versatility & mobility (comes with a hook)
- ☆ PU baffle compatible with solvent
- ☆ Wide-mouth opening for easier cleaning (2QT-S)
- ☆ Detachable lock ring, free from tangled hoses (2QT-S)



10L or Larger

- ☆ One-piece stainless steel construction and parts; free from corrosion.
- ☆ Patented "butterfly" locking nuts for maximum safety & durability
- ☆ Air distribution valve under lid to prevent paint splash
- ☆ Non-agitation, or Manual/Air-Motored agitation models
- ☆ Ideal for both solvent and water-based material
- ☆ Optional aluminum or stainless steel interior container for easier maintenance
- ☆ Available in 2, 10, 20, 50 Liters (1 Liter = 0.25 Gallon)



SANDER & GRINDER



RANDOM ORBITAL PALM SANDER (5mm ORBIT)

S-5N / S-6N (5"/6", Non-Vacuum)
S-5C / S-6C (5"/6", Central-Vacuum)
S-5S / S-6S (5"/6", Self-Generated Vacuum)



ANGLE DIE GRINDER

S-210 or S-210Kit (30 pcs Disc/Pad/Stone)



100° HEAVY DUTY GRINDER

S-HDG4 (inch)
S-HDG5 (inch)

STRAIGHT DIE GRINDER

S-200 or S-200Kit (30 pcs Disc/Pad/Stone)

ACCESSORIES

